

AuLED 20

System of protection	IP67
Series	surface lamp
Dimension	22 x 90 x 540 mm
Cover plate	ESG - glass = toughened safety glass
Power	24 W
Voltage	24 V/DC
Luminous	3100 Lumen
Item nos.	592-502-001 (M8-plug side) 592-502-002 (M8-plug behind) 592-502-011 (M12-plug side) 592-502-012 (M12-plug behind)

CHARACTERISTICS

- Very robust Al-box
- Toughened safety glass
- Plug connection M8 or M12 behind or at side
- LED-lamp
- Glass cover and LED board can be easily exchanged



AuLED 20



TYPE	COVER PLATE	ITEM NO.	POWER	LUMINOUS	DIMENSION / MM	VOLTAGE	PLUG
AuLED 20	ESG	592-502-001	24 W	3100	22 x 90 x 540	24 V/DC	M8-side
AuLED 20	ESG	592-502-002	24 W	3100	22 x 90 x 540	24 V/DC	M8-behind
AuLED 20	ESG	592-502-011	24 W	3100	22 x 90 x 540	24 V/DC	M12-side
AuLED 20	ESG	592-502-012	24 W	3100	22 x 90 x 540	24 V/DC	M12-behind

ACCESSORIES OPTIONAL



Power supply stabilized
Power: 30 W
Item no.: 213-820-212
Voltage: 100-240 V / 50-60 Hz /
24 V/DC

Connection cable for plug connection M8
Item no.: 214-100-001

Cable Box for plug connection M12
Item no.: 213-080-040

DRAWING

